## CLAIMS

- 1) A screw anchor (1) having a deformable central portion (2) in which four main longitudinal slots (8) are formed; said screw anchor (1) being characterized by comprising a number of secondary longitudinal slots (10) formed in said central portion (2).
- 2) A screw anchor as claimed in Claim 1, characterized in that each said secondary longitudinal slot (10) defines, on said central portion (2) and with an adjacent main longitudinal slot (8) and/or an adjacent secondary longitudinal slot (10), respective deformable secondary longitudinal anchoring tongues (11).

10

25

- 3) Α screw anchor as claimed in Claim 1, that pairs of said four characterized in 15 longitudinal slots (8) define on said central portion (2) respective deformable main longitudinal anchoring tongues (9).
- 4) A screw anchor as claimed in Claim 2,
  20 characterized in that each said deformable secondary
  longitudinal anchoring tongue (11) has a substantially
  serrated profile.
  - claimed 5) Α anchor as in Claim 3, screw in that each said deformable characterized longitudinal anchoring tongue (9) has a substantially serrated profile.
  - 6) A screw anchor as claimed in Claim 1, characterized in that said main longitudinal slots (8)

are spaced angularly apart on said central portion (2).

- 7) A screw anchor as claimed in Claim 6, characterized in that said main longitudinal slots (8) are spaced angularly apart.
- 8) A screw anchor as claimed in Claim 1, characterized in that said secondary longitudinal slots (10) face and are coplanar with one another in pairs.

5

10

15

20

- claimed 9) Α screw anchor as in Claim 8, characterized in that each secondary longitudinal slot (10)equidistant from the 'two adjacent is main longitudinal slots (8).
- 10) A screw anchor as claimed in Claim 1, characterized by comprising a collar (3) at a first end of said central portion (2); said collar (3) having an annular flange (5) coaxial with said longitudinal axis (A).
- 11) A screw anchor as claimed in Claim 10, characterized by comprising a number of equally spaced projecting appendixes (6) integral with said collar (3) and extending parallel to said longitudinal axis (A).
- 12) A screw anchor as claimed in Claim 10, characterized by comprising a head (4) at a second end of said central portion (2).
- 13) A screw anchor as claimed in Claim 1,
  25 characterized by comprising a through hole (7) coaxial
  with said longitudinal axis (A); said through hole (7)
  having, internally, a number of longitudinal ribs (12)
  parallel to said longitudinal axis (A).